

PIO-CAN



Features:

1. Filter monitor: Back pressure and exhaust gas temperature with alarm, pre alarm and AD-values (for sensor check). Monitoring, RPM, min.-max. alarms and adjustable delay timers.
Alarms: optical with alphanumeric messages and buzzer.
 2. Adjustable alarm relay: For external signals, i.e. flashing lights or engine shut down function.
 3. Recording: Operational and failures including date and time, tamper resistant, print in TXT file format.
 4. Datalogger: Maximum of 8 channels with variable configuration. High logging memory: up to 1,248 operation hours.
 5. Fuel additive Dosing: Full automatically additive dosing control and monitoring for DPFiS systems.
 6. Electrical Regeneration: Control and monitor of the electrical regeneration system DPFi for on-board and off-board units.
 7. Power supply: 12-24VDC with zero power consumption in stand-by mode.
 8. Connectors: Company Deutsch type connectors.
 9. More features:
 - CE-mark
 - Cabling available in other lengths (option)
 - Heavy duty case protection class IP65
 - High quality pressure sensor and thermocouple
 - Easy installation
- Option: Remote control.

Please contact us for further information.

**Johnson Matthey GmbH
Otto-Volger-Straße 9b
D-65843 Sulzbach /Ts.**

**Tel: 06196 703813
Fax: 06196 72450**

Email: oliver.vehmeier@matthey.com

